

Product data sheet

Specifications



APC Netshelter Rack Automatic Transfer Switch, 2U, 30A, 200/208V, 2 L6-30 IN, 16 C13, 2 C19 OUT, 50/60Hz

AP4432A

Main

Product or Component Type	Automatic transfer switch
Main Input Voltage	200 V AC 1 phase 208 V
Input current limits	30 A
Input Frequency	50/60 Hz
Main Output Voltage	200 V AC 1 phase 208 V
Input Connection Type	NEMA L6-30P 24 A 2P+E
Load Capacity	4992 VA
Line Rated Current	30 A
permissible voltage	180...220 V
Max current draw	30 A
Max line current	30 A
Protection Type	Circuit breaker
Number of rack unit	2U
Number of cables	2
Cable length	7.97 ft (2.43 m)
Cord Length	8.005 ft (2.44 m)
Provided Equipment	Mounting Hardware Rack Mounting brackets

Complementary

Mounting Location	Front Rear
Mounting Mode	Rack-mounted
Mounting position	Horizontal
Color	Black
Height	3.5 in (88 mm)
Width	17.008 in (432 mm)
Depth	9.3 in (236 mm)
Net Weight	14.51 lb(US) (6.58 kg)

Environmental

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product Certifications	PSE TÜV-C TÜV-NURTL
Standards	EN 55022 Class A FCC Part 15 class A
Relative Humidity	5...95 %
Storage Relative Humidity	5...95 %
Ambient Air Temperature for Storage	-13...149 °F (-25...65 °C)
Storage altitude	0...50000 ft (0...15240 m)
Operating altitude	0...10000 ft
Ambient Air Temperature for Operation	23...113 °F (-5...45 °C)

Ordering and shipping details

GTIN	731304432487
------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	8.3 in (21 cm)
Package 1 Width	23.0 in (58.4 cm)
Package 1 Length	14.02 in (35.6 cm)
Package weight(Lbs)	20.00 lb(US) (9.07 kg)

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	2 111 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	91 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.9 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	2 014 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	4 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Average percentage of recycled plastic content	10 %
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen content performance	Product contains halogen above thresholds

Use Again



Repack and remanufacture

Recyclability potential, in %	55
Circularity Profile	End of Life Information
Removable battery	Yes
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

